

AC6368B Datasheet

Zhuhai Jieli Technology Co.,LTD

Version: V1.2

Date: 2024.03.06

AC6368B Features

CPU

- 32-bit DSP supports hardware Float Point Unit (FPU)
- Up to 160MHz programmable processor
- 64 Vectored interrupts
- 4 Levels interrupt priority

Bluetooth

- Compliant with Bluetooth V5.4+BR+EDR+BLE specification
- Meet class1 class2 and class3 transmitting power requirement
- Support GFSK and $\pi/4$ DQPSK all packet types
- Provides +6dbm transmitting power
- receiver with -90dBm sensitivity
- Fast AGC for enhanced dynamic range
- Supports
a2dp\avctp\avdtp\avrcp\hfp\spp\smp\att\gap\gatt\rfcomm\sdp\l2cap profile

Temperature

- Operating temperature: -40°C to +85°C
- Storage temperature: -65°C to +150°C

Peripherals

- One full speed USB 2.0 OTG controller
- Six multi-function 32-bit timers, support capture and PWM mode
- Three full-duplex basic UART, UART0 and UART1 supports DMA mode
- One hardware IIC interface supports host and device mode
- 10-bit ADC for analog sampling
- External wake up/interrupt on all GPIOs

PMU

- Low voltage LDO for internal digital and analog circuit supply
- 3uA current consumption in the soft-off mode
- Built-in LDO for the core, I/O, Bluetooth and flash
- VBAT is 2.2V to 5.5V
- VDDIO is 2.2V to 3.4V

Packages

- SOP8

Applications

- Bluetooth IOT

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

1、 Pin Definition

1.1 Pin Assignment




Figure 1-1 AC6368B Package Diagram

1.2 Pin Description

Table 1-1 AC6368B Pin Description

PIN NO.	Name	I/O Type	Drive (mA)	Function	Other Function
1	VBAT	P	/		Battery Power Supply
2	VDDIO	P	/		IO Power 3.3v
3	VSS	P	/		Ground
4	BT_RF	/			BT Antenna
5	BTOSCI	I			BT OSC In
6	BTOSCO	O			BT OSC Out
7	USBDM	I/O		USB Negative Data (pull down)	IIC_SDA_A: IIC SDA(A); SPI2_DOB: SPI2 Data Out(B); ADC14: ADC Input Channel 14; UART1RXD: Uart1 Data In(D);
8	USBDP	I/O		USB Positive Data (pull down)	IIC_SCL_A: IIC SCL(A); SPI2_CLKB: SPI2 Clock(B); ADC13: ADC Input Channel 13; UART1TXD: Uart1 Data Output(D);
	PA6	I/O		GPIO	ADC4: ADC Input Channel 4; CAP4: Timer4 Capture; UART0RXA: Uart0 Data In(A);

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2、Electrical Characteristics

2.1 Absolute Maximum Ratings

Table 2-1

Symbol	Parameter	Min	Max	Unit
T _{opt}	Operating temperature	-40	+85	°C
T _{stg}	Storage temperature	-65	+150	°C
V _{BAT}	Supply Voltage	-0.3	5.5	V
V _{3.3IO}	3.3V IO Input Voltage	-0.3	3.6	V

Note : The chip can be damaged by any stress in excess of the absolute maximum ratings listed below

2.2 Recommended Operating Conditions

Table 2-2

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
V _{BAT}	Voltage Input	2.2	3.7	5.5	V	
V _{VDDIO}	Voltage Input	–	3.0	–	V	

2.3 IO Input/Output Electrical Logical Characteristics

Table 2-3

IO input characteristics						
Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
V _{IL}	Low-Level Input Voltage	-0.3	–	0.3* VDDIO	V	VDDIO = 3.3V
V _{IH}	High-Level Input Voltage	0.7* VDDIO	–	VDDIO+0.3	V	VDDIO = 3.3V
IO output characteristics						
V _{OL}	Low-Level Output Voltage	–	–	0.33	V	VDDIO = 3.3V
V _{OH}	High-Level Output Voltage	2.7	–	–	V	VDDIO = 3.3V

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2.4 Internal Resistor Characteristics

Table 2-4

Port	General Output	High Drive	Internal Pull-Up Resistor	Internal Pull-Down Resistor	Comment
PA6	8mA	24mA	10K	10K	1、USBDM & USBDP default pull down 2、internal pull-up/pull-down resistance accuracy $\pm 20\%$
USBDP	4mA	-	1.5K	15K	
USBDM	4mA	-	180K	15K	

2.5 BT Characteristics

2.5.1 Transmitter

Basic Rate

Table 2-5

Parameter		Min	Typ	Max	Unit	Test Conditions
RF Transmit Power		-	4	6	dBm	25°C, Power Supply
RF Power Control Range		-	20	-	dB	
20dB Bandwidth		-	950	-	KHz	
In-band spurious Emissions (BQB Test Mode RF_Tx Power=4dBm)	F=F ₀ ±1MHz	-	-20	-	dBm	VBAT=3.7V 2441MHz DH5
	F=F ₀ ±2MHz	-	-45	-	dBm	
	F=F ₀ ±3MHz	-	-35	-	dBm	
	F=F ₀ ±>3MHz	-	-45	-	dBm	

Enhanced Data Rate

Table 2-6

Parameter		Min	Typ	Max	Unit	Test Conditions
Relative Power		-	-1	-	dB	25°C, Power Supply
$\pi/4$ DQPSK	DEVM RMS	-	4	-	%	
	DEVM 99%	-	10	-	%	
Modulation Accuracy		-	7	-	%	VBAT=3.7V 2441MHz 2DH5
In-band spurious Emissions (BQB Test Mode RF_Tx Power=4dBm)	F=F ₀ ±1MHz	-	-4	-	dBm	
	F=F ₀ ±2MHz	-	-30	-	dBm	
	F=F ₀ ±3MHz	-	-30	-	dBm	
	F=F ₀ ±>3MHz	-	-37	-	dBm	

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2.5.2 Receiver

Basic Rate

Table 2-7

Parameter		Min	Typ	Max	Unit	Test Conditions
Sensitivity		-	-88	-	dBm	25°C, Power Supply VBAT=3.7V 2441MHz DH5
Co-channel Interference Rejection		-	6	-	dB	
Adjacent Channel selectivity C/I	+1MHz	-	-6	-	dB	
	-1MHz	-	-8	-	dB	
	+2MHz	-	-17	-	dB	
	-2MHz	-	-21	-	dB	
	+3MHz	-	-15	-	dB	
	-3MHz	-	-31	-	dB	

Enhanced Data Rate

Table 2-8

Parameter		Min	Typ	Max	Unit	Test Conditions
Sensitivity		-	-90	-	dBm	25°C, Power Supply VBAT=3.7V 2441MHz 2DH5
Co-channel Interference Rejection		-	9	-	dB	
Adjacent Channel selectivity C/I	+1MHz	-	-10	-	dB	
	-1MHz	-	-13	-	dB	
	+2MHz	-	-11	-	dB	
	-2MHz	-	-21	-	dB	
	+3MHz	-	-13	-	dB	
	-3MHz	-	-40	-	dB	

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2.5.3 BLE

1M Data Rate

Table 2-9

Parameter		Min	Typ	Max	Unit	Test Conditions
Sensitivity		-	-91	-	dBm	25°C Power Supply VBAT=3.7V 2440MHz
RF Transmit Power		-	6	-	dBm	
In-band Spurious Emission	M-N =2MHz	-	-41	-	dBm	
	M-N ≥3MHz	-	-40	-	dBm	
Modulation Characteristics	Δf1 avg	-	250	-	KHz	
	Δf2 99%	-	210	-	KHz	
	Δf1avg/Δf2avg	-	0.9	-	/	
Carrier Frequency Offset		-50	-	+50	KHz	
Frequency Drift		-25	-	+25	KHz	
Frequency Drift Rate		-5	-	+5	KHz/50us	

2M Data Rate

Table 2-10

Parameter		Min	Typ	Max	Unit	Test Conditions
Sensitivity		-	-89	-	dBm	25°C Power Supply VBAT=3.7V 2440MHz
RF Transmit Power		-	6	-	dBm	
In-band Spurious Emission	M-N =4MHz	-	-45	-	dBm	
	M-N =5MHz	-	-45	-	dBm	
	M-N ≥6MHz	-	-45	-	dBm	
Modulation Characteristics	Δf1 avg	-	500	-	KHz	
	Δf2 99%	-	430	-	KHz	
	Δf1avg/Δf2avg	-	0.9	-	/	
Carrier Frequency Offset		-50	-	+50	KHz	
Frequency Drift		-25	-	+25	KHz	
Frequency Drift Rate		-5	-	+5	KHz/50us	

Long Range

Table 2-11


Parameter	Min	Typ	Max	Unit	Test Conditions
Sensitivity LE 125K(S8)	-	-99	-	dBm	VBAT=3.7V,25°C
Sensitivity LE 500K(S2)	-	-95	-	dBm	2440MHz

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

3、 Package Information

3.1 SOP8



Symbol	Dimension In Millimeters		Dimension In Inches	
	Min	Max	Min	Max
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.007	0.010
D	4.700	5.100	0.185	0.201
E	3.800	4.000	0.150	0.157
E1	5.800	6.200	0.228	0.244
e	1.27TYP		0.050TYP	
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°

Figure 3-1 AC6368B Package

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

4、 Revision History

Date	Revision	Description
2020.07.03	V1.0	Initial Release
2022.07.19	V1.1	Update Bluetooth Feature
2024.03.06	V1.2	Update Bluetooth Feature, Add BLE Parameter

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.